

MADAN PUMPS



UNI-CUB

The compact, sturdy and time proved series of **Madan** air-operated pumps, are principally designed for pressure testing application but are also used by many OEM customers. The smallest in the **Madan** pump range, the **Uni-Cub**, offers:

- Seven models ranging from 28 bar to 1,080 bar.
- Volume outputs from 0 to 14 litres/minute.
- Minimum air pressure required to start pump will be up to 1 bar.
- Available in portable pressure test packages.
- Measures only 213mm high x 156mm diameter
- Stainless steel wetted parts

UNI-CUB MODEL	A	B	C	D	E	F	G
RATIO 1:	4.3	11.9	26.7	47.5	68.4	107	163
OUTPUT/CYCLE CC	28	10	4.5	2.5	1.7	1.1	0.7
MAX. FREE FLOW litres/minute	14	5	2.4	1.4	0.9	0.6	0.4
MAX. OUTPUT PRESSURE (BAR)	28	79	175	315	455	710	1080

The **Madan Mark 7** air driven pumps, are a tried and tested series of units designed to deliver a wide range of fluids to pressures up to 2440 bar. The range features :-

- Twelve models ranging from 27-2440 bar.
- Volume outputs from 0 to 37 litres/minute.
- Minimum air pressure required to start pump will be up to 1 bar.
- Available in portable pressure test packages.
- Measures only 305mm high x 267mm diameter.
- Stainless steel wetted parts.



MARK 7

MARK 7 RATIO 1:	4	9	13.6	19	28.4	36	54.5	76.5	113	145	256	368
OUTPUT/CYCLE CC	160	70	50	34	23	18	12	8	6	4	2.5	1.7
MAX. FREE FLOW litres/minute	37	23	15	11	7.3	5.8	3.8	2.8	1.8	1.5	0.84	0.58
MAX. OUTPUT PRESSURE (BAR)	27	60	90	126	188	240	360	510	750	964	1700	2440

Hydraulic Pneumatic Services Ltd, Unit 17, King St Trading Est.
Middlewich, Cheshire, CW10 9LF, United Kingdom.

Tel: (0)1606 835725 Fax: (0)1606 737358 www.madan.uk.com